



EN 14785  
BlmSchV Stufe 2  
Regensburger BStV / Aachener BStV / Munchener BStV  
ART.15a B-VG / LRV  
4 stelle DM.186 / Conto Termico 2.0



<b>(Max) nominal heat output</b>	<b>6.3 kW</b>
<b>Minimum heat output</b>	<b>2.4 kW</b>
<b>Efficiency at Max</b>	<b>91 %</b>
<b>Efficiency at Min</b>	<b>96.9 %</b>
<b>Energy Efficiency Class (A++ / G scale)</b>	<b>A+</b>
<b>Energy Efficiency Index (EEI)</b>	<b>121 %</b>
<b>Seasonal space heating energy efficiency (ηs)</b>	<b>80 %</b>
<b>Temperature of exhaust smoke at Max</b>	<b>135 °C</b>
<b>Temperature of exhaust smoke at Min</b>	<b>75 °C</b>
<b>Particulate/OGC / Nox (nominal at 13%O2)</b>	<b>14 - 1 - 108 mg/Nm3</b>
<b>CO at 13% O<sub>2</sub> at Min and at Max</b>	<b>0.032 - 0.008 %</b>
<b>CO<sub>2</sub> at Min and at Max</b>	<b>9.8 - 10.7 %</b>
<b>Recommended draught at Max power</b>	<b>10 Pa</b>
<b>Minimum draught allowed for minimum power</b>	<b>5 Pa</b>
<b>Mass of smoke at Min and at Max</b>	<b>1.8 - 4.6 g/sec</b>
<b>Hopper capacity</b>	<b>20 l</b>
<b>Fuel dimensions</b>	<b>Ø 6mm L 3 ÷ 40mm</b>
<b>Hourly consumption at Min and at Max</b>	<b>0.51 - 1.43 kg/h *</b>
<b>Autonomy at Min and at Max</b>	<b>25 - 9 h *</b>
<b>Heatable volume m<sup>3</sup></b>	<b>115 - 180 - 315 **</b>
<b>Air inlet</b>	<b>80 cm<sup>2</sup></b>
<b>Smoke outlet</b>	<b>Ø 80/130 mm</b>
<b>Nominal electrical power (EN 60335-1).</b>	<b>48 W (max 350 W)</b>
<b>Supply voltage and frequency</b>	<b>230 Volt / 50 Hz</b>
<b>Net weight</b>	<b>103 kg</b>
<b>Distance from combustible material (back/side/under)</b>	<b>150 mm / 150 mm / 0 mm</b>
<b>Distance from combustible material (front/ceiling)</b>	<b>800 mm / 1000 mm</b>

\* Data that may vary depending on the type of pellets used.

\*\*Heatable volume based on the requested power per m<sup>3</sup> (respectively 55-35-20 W/m<sup>3</sup>)